



 **GESCHIRRSPÜLER 500 DOPPELWANDIG MIT INTEGRIERTER WASSERENTHÄRTUNG UND ABLAUFPUMP**

- Gehäuse, Rückwand und Wanne aus Edelstahl 18/10
- Wasch- und Spülarme aus Edelstahl
- Türkontaktschalter
- Türe doppelwandig
- Incoloy 800 Tank- und Bolierheizung
- Leistung / h : 20 - 30 Körbe
- Korbabmessung : 500 x 500 mm
- Stromversorgung 400 V / 50 Hz
- Tankheizung 2 kW
- Boilerheizung 5,2 kW
- Selbstentleerender Tank
- Klarspüldosierer
- Trockenlaufschutz
- Wasserverbrauch : 3 Liter
- Tankinhalt : 21 Liter
- Festwasseranschluss : G3/4'
- Abfluss Ø 28 mm
- Inklusive 2 Körben
- Zykluszeit 120/180 Sekunden
- Leistung : 5,7 kW
- Abmessungen : L 600 x T 620 x H 828 mm
- Gewicht : 69 Kg

Artikelreferenz : CLVADPVADB  
EAN : 3611630078986

 **DISHWASHER DOUBLE WALLED DOOR WITH DRAIN PUMP AND WATER SOFTENER**

- Frame and wall in stainless steel AISI 304
- Wash arm
- Double wall door
- Safety door contact
- Superheater and tank heating element Incoloy 800
- Drain pump
- Water softener
- Protection against dry running
- Rinse aid dispenser
- Auto draining tank
- Power of tank heating element: 2 kW
- Power of superheater: 6.1 kW
- Water connexion G3/4M
- Runoff: Ø 28 mm
- Electric pump with Soft-Start
- Water consumption: 3 liters
- Tank's capacity: 21 liters
- Performance: 20/30/60 baskets per hour or 10 baskets per hour
- Cycle duration: 60/120/180 seconds
- Basket: 500 x 500 mm
- Endowment: 2 baskets
- Electric supply: 400 V / 50 Hz
- Power: 6.4 kW
- Dimensions: W 600 x D 620 x H 828 mm
- Weight: 73 kg

Article reference : CLVADPVADB  
EAN : 3611630078986